

MSDS 1108 Rubber Base Solvent  
MATERIAL SAFETY DATA SHEET  
FOR COATINGS, RESINS AND RELATED MATERIALS  
DATE OF PREPARATION - 01-01-10

PAGE #1

MANUFACTURER'S NAME : Kelley Technical Coatings  
ADDRESS : 1445 South 15th Street  
ADDRESS : PO Box 3726  
ADDRESS :  
CITY, STATE : Louisville, Kentucky, 40201-3726

EMERGENCY TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (800) 424-9300-  
INFORMATION TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (502) 363-9721-

-----  
SECTION I -- PRODUCT IDENTIFICATION  
-----

MANUFACTURER'S CODE IDENTIFICATION :X1108  
PRODUCT CLASS : Aromatic Solvent  
TRADE NAME : Rubber Base Solvent  
HMIS INFORMATION : HEALTH : 02  
FLAMMABILITY : 02  
REACTIVITY : 01  
PERSONAL PROTECTIVE EQUIPMENT : REFER TO "SECTION VIII"

-----  
SECTION II -- HAZARDOUS INGREDIENTS  
-----

----- INGREDIENT -----		%BY	ACGIH	OSHA	SAR NUIS
MATERIAL DESCRIPTION Cas		WEIGHT	T.L.V.	P.E.L	313 PGMT
AROMATIC NAPHTHA					
	64742-95-6	100	100PPM	100PPM	Y N

If indicated above; this material could constitute a personnel hazard.

If the CAS# field above starts with ## then this material is considered a trade secret.

-----  
SECTION III -- PHYSICAL DATA  
-----

LOWER EXPLOSION LEVEL		1.0 - 1.2	
BOILING RANGE	HIGH	335 DF	LOW 306 DF
VAPOR PRESSURE		3.00 MMHG @ 68DF	
VAPOR DENSITY		HEAVIER THAN AIR	
EVAPORATION RATE		SLOWER THAN BUTYL ACETATE	
WEIGHT PER GALLON		7.29	
% VOLATILE BY VOLUME		100	
% VOLATILE BY WEIGHT		100	
VOC	---	LBS/GAL	LBS/GAL No Water 7.29
		GRAMS/LITER	GRAMS/LITER 874.8

-----  
SECTION IV -- FIRE AND EXPLOSION DATA  
-----

MATERIAL SAFETY DATA SHEET

PAGE #2

MANUFACTURER'S CODE X1108  
TRADE NAME Rubber Base Solvent,

DATE OF PREPARATION - 01-01-06

FLAMMABILITY CLASSIFICATION OSHA - CLASS II  
DOT - COMBUSTIBLE LIQUID UN 1263  
LOWEST FLASH POINT T.C.C. 110 DF  
LOWER EXPLOSION LEVEL (LEL) 1%

MSDS 1108 Rubber Base Solvent

Extinguishing Media: (Yes) - Foam (No) - Alcohol Foam (Yes) - CO2  
(Yes) - Dry Chemical (Yes) - Water Fog  
Unusual Fire and Explosion Hazards: - Flammable vapors may form explosive mixtures with air.  
Special Fire Fighting Procedures: - Avoid solid stream of water, use fog for cooling.

-----  
SECTION V -- HEALTH HAZARD DATA  
-----

To the best of our knowledge, this product does not contain any carcinogenic ingredients.  
Effects of Overexposure: - Liquid may cause eye burns. Prolonged skin contact with liquid may cause irritation. Eye, nose and throat irritation may result from exposure to vapor. Narcotic effects occur at higher concentrations of vapor.  
Primary Route(s) of Entry: (X) - Dermal (X) - Inhalation (X) - Ingestion  
Emergency and First Aid Procedures:  
- Eye contact: Irrigate immediately and thoroughly with water at least 15 minutes and get medical attention.  
- Skin contact: Flush immediately and thoroughly with water.  
- Inhalation: Remove from exposure, treat symptomatically and get medical attention.  
Medical Conditions Prone to Aggravation by Exposure:  
- Pre-existing Respiratory, Eye and Skin Conditions.

-----  
SECTION VI -- REACTIVITY DATA  
-----

Stability: ( ) - Unstable (X) - Stable  
Hazardous Polymerization: ( ) - May Occur (X) - will Not Occur  
Hazardous Decomposition Products: - As with any other organic material, combustion will produce carbon dioxide and probably carbon monoxide.  
Conditions to Avoid: - Not applicable.  
Incompatibility (Materials to Avoid): - Oxidizing materials can cause a vigorous reaction.

MATERIAL SAFETY DATA SHEET

PAGE #3

MANUFACTURER'S CODE X1108 DATE OF PREPARATION - 01-01-06  
TRADE NAME Rubber Base Solvent,

-----  
SECTION VII -- SPILL OR LEAK PROCEDURES  
-----

Steps to be Taken in Case Material is Leaked or Spilled:  
- Eliminate all ignition sources. Flush spill away with water spray.  
- Small spills may be collected with absorbant material.  
Waste Disposal Method:  
- Mix with a compatible chemical which is less combustibile and incinerate.  
- Observe all federal, state, and local laws concerning health and pollution.

-----  
SECTION VIII -- SAFE HANDLING AND USE INFORMATION  
-----

Respiratory Protection: - A NIOSH approved respirator for organic vapors should be worn if needed.  
Ventilation: - Local exhaust recommended.  
- Mechanical (General) recommended.  
- Special: None known.  
Protective Gloves: - Should be worn.  
Eye Protection: - Safety glasses should be worn in any type of industrial operation.

MSDS 1108 Rubber Base Solvent

Other Protective Equipment: - Safety shower and eye bath in work area.  
Hygienic Practices: - Remove paint from skin contact after exposure.

---

SECTION IX -- SPECIAL PRECAUTIONS

---

Precautions to be Taken in Handling and Storing: - Material is classified as a flammable liquid. Keep away from heat, sparks and open flame. Keep container closed. Avoid eye contact, prolonged skin contact, and inhalation of high concentrations of vapor. Use with ventilation adequate to maintain vapor concentrations below the TLV of 50 PPM.  
Other Precautions: - Hazardous product residue may remain after the product has been removed from its container. Do not reuse "empty" container without commercial cleaning or reconditioning. See also 29 code of federal regulation 1910.1000.